

EASY TO USE DURABLE LIGHTWEIGHT



- Sealed up to IP68
- Over 5,000 mating cycles
- Resistant to large temperature variations
- Clear coding for easy operation

Ideally suited for:

- Medical applications
- Industrial & instrumentation
- Food and pharmaceutical processing







THE RELIABLE EXPERT

AVAILABLE **SERIES**



405

(2 to 27 contacts)



PLUGS

CABLE MOUNTED		
BODY STYLES	S	SI
Locking system	Push-pull	Push-pull
Sealing	IP50 / IP67	IP50 / IP67
Design	Standard	Standard
Integral shielding	Yes	No

RECEPTACLES

PANEL FRONT
MOUNTED

Sealing	IP50	
BODY STYLES	DBP	
MOUNTED		

4032

(2 to 19 contacts)



PLUGS

Sealing Design

CABLE MOUNTED



No

Standard

MOUNTED		
BODY STYLES	SI	
Locking system	Push-pull	
Sealing	IP50 / IP68	
Design	Standard	

RECEPTACLES

Integral shielding

PANEL FRONT MOUNTED	6	6
BODY STYLES	DBP	DBPO
Sealing	IP50	IP68
Design	Standard	Standard

 Sterilizable* by Autoclave, Cidex, EtO, gamma radiation, Steris[®] or Sterrad[®]

Lightweight and easy to handle

Integrated into FDA-approved medical devices

• EMI/RFI shielding for reliable data transmission

PERFORMANCE & RELIABILITY



*Only for the 405 Series



scher

© Fischer Connectors SA - All rights reserved - 550100 - version 1.0 - 06.2016 - Changes without prior notice